

from [recruitment.wsdl](#)

- "language" attribute - [ListLanguages](#)
- "skill" attribute - [ListSkills](#)

example:

```
<persistence-request operationId='ListGrades'>
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:xsi="http://www.w3.org/2001/XMLSchema-
instance">
  <SOAP-ENV:Body>
    <impl:ListGrades xmlns:impl="http://atollon.com/enterprise/wsdl">
      <server>atollon</server>
      <session>66861ADB26BACD1D752328FFA53C2740E19BEF34BD04</session>
      <language>2508000</language>
      <skill>64508000</skill>
    </impl:ListGrades>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
</persistence-request>
```

```
<persistence-response operationId='ListGrades'>
<atollon:ListGradesResponse xmlns:atollon="http://iterity.com/enterprise/wsdl"
xmlns:soapenv="http://schemas.xmlsoap.org/soap/envelope/">
  <result>OK</result>
  <time>0.19080710</time>
  <count>5</count>
  <ROWS>
    <ROW>
      <id>64580000</id>
      <acl>SKGD000000002155</acl>
      <name>64579000</name>
      <candidates_num>0</candidates_num>
      <treeHandle>1671000</treeHandle>
      <skill>64508000</skill>
      <language>2508000</language>
      <text>1</text>
      <languageShort>ENG</languageShort>
      <languageLong>English</languageLong>
      <value>20</value>
    </ROW>
    <ROW>
      <id>64582000</id>
      <acl>SKGD000000002156</acl>
      <name>64581000</name>
      <candidates_num>0</candidates_num>
      <treeHandle>1671000</treeHandle>
```

```
<skill>64508000</skill>
<language>2508000</language>
<text>2</text>
<languageShort>ENG</languageShort>
<languageLong>English</languageLong>
<value>40</value>
</ROW>
...
</ROWS>
</atollon:ListGradesResponse>
</persistency-response>
```